







Vacupor® und VACUSPEED®












Vacuum Insulation for the building industry

approved by the German Institute for Building Technology (DIBt)

	<p>Vacuspeed® rated value: 0,008 W / (m × K)</p>
	<p>Vacupor® NT-B2-S rated value: 0,007 W / (m × K) Vacupor® NT-B2 rated value: 0,008 W / (m × K) no lamination</p>
	<p>Vacupor® RP-B2-S rated value: 0,007 W / (m × K) Vacupor® RP-B2 rated value: 0,008 W / (m × K) lamination with rubber granule</p>
	<p>Vacupor® PS-B2-S* rated value: 0,007 W / (m × K) Vacupor® PS-B2* rated value: 0,008 W / (m × K) lamination with polystyrene</p>
	<p>Vacupor® XPS-B2-S rated value: 0,007 W / (m × K) Vacupor® XPS-B2 rated value: 0,008 W / (m × K) lamination with extruded polystyrene</p>
	<p>Vacupor® TS-B2-S rated value: 0,007 W / (m × K) Vacupor® TS-B2 rated value: 0,008 W / (m × K) lamination with synthetic recycling sound absorption material</p>

*Vacupor® PS-B2 and Vacupor® PS-B2-S have no approved application for application area: DAA

approved application areas:

	<p>DAD exterior insulation of roof or ceiling; saved of weathering; insulation under covering</p>
	<p>DAA exterior insulation of roof or ceiling; saved of weathering; insulation under sealing</p>
	<p>DZ insulation between rafters; double layer roof system; not walkable; accessible top floor ceiling</p>
	<p>DI interior insulation of roof or ceiling; insulation under supporting rafters / structure, suspending ceiling, etc. ...</p>
	<p>DEO interior insulation of roof or ceiling; under screed without sound absorption requirements</p>
	<p>WAB exterior insulation of walls under covering</p>
	<p>WAA exterior insulation of walls under sealing</p>
	<p>WH insulation of wooden frames and wooden plate constructions</p>
	<p>WI interior insulation</p>
	<p>WTR insulation of partition walls</p>
	<p>insulation of prefabricated facade elements; with insulated glass character</p>